

Cyclone (GC)

FEATURES


- 1 Manual rotation (MR) models can be locked into one of four positions
- 2 Short, two-piece rock shield allows use in narrower trenches
- 3 Pin-on carbide teeth rotate while cutting to allow even wear and a better grinding point
- 4 Fully enclosed hydraulic components
- 5 Heavy-duty hydraulic motor and gearbox with a direct drive system ensure solid performance



APPLICATIONS

- Trenching
- Quarry Work
- Demolition
- Tunneling & Mine Work
- Soil Remediation
- Lock & Dam Reconstruction
- Concrete Milling/Resurfacing
- Waterfront Rejuvenation

TRENCHING DETAILS



The Genesis Cyclone can generate a minimum trench width of 32.5" or 40", depending on model.

Metric Specs:

Model	Weight*	Overall Height	Overall Width	Drum Width	Drum Diameter w/ Teeth	Minimum Excavator Wt.
	(kg)	(mm)	(mm)	(mm)	(mm)	(mt)
GC 550	2,517	1,461	1,207	610	826	31
GC 550MR	2,812	1,638	1,207	610	826	31
GC 950	3,629	1,778	1,461	889	1,016	45
GC 950MR	3,992	1,956	1,461	889	1,016	45

*Weight includes mounting bracket to attach to excavator.

All Genesis MR model Cyclones feature manual rotation capability.

All Genesis Cyclones are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.